

Soho

GENERAL INFORMATION

Composition	100% PES
Weight g/m ²	420g
Weight g/Lm	609g
Width	145cm
Min. usable Width	138cm
Piece Length	40m
Tariff code	54079200

CLEANING INSTRUCTIONS



TECHNICAL DATE

• SHRINKAGE	40° WARP	-1.25%
	WEFT	-0.44
• MARTINDALE ABRASION ISO12947-2 1998	END POINT	90000
	CHANGE IN COLOR	4/5
• SEAM SLIPPAGE EN ISO 13936-2	WARP	2.5
	WEFT	3
• TEAR STRENGHT EN ISO 13937-3:2000	WARP	155N
	WEFT	140N
• TENSILE STRENGHT ISO 13934-1	WARP	1100N
	WEFT	1700N
• COLOUR FASTNESS FOR RUBBING EN ISO 105-X12	WARP DRY	4/5
	WARP WET	4
	WEFT DRY	4/5
	WEFT WET	4
• COLOUR FASTNESS TO LIGHT EN ISO 105-B02	GRADE	100: 4
	GRADE	101: 4
	GRADE	103: 4/5
	GRADE	104: 4
	GRADE	201: 4/5
	GRADE	203: 5
	GRADE	302: 5
	GRADE	308: 5
	GRADE	404: 5
	GRADE	405: 5
	GRADE	501: 3/4
	GRADE	502: 3/4
	GRADE	504: 4
	GRADE	505: 4
	GRADE	601: 3/4
	GRADE	604: 4
	GRADE	606: 4

	GRADE	607: 4
	GRADE	608: 5
	GRADE	700: 4/5
	GRADE	703: 4
	GRADE	706: 3/4
	GRADE	713: 4
	GRADE	800: 4
	GRADE	801: 5
	GRADE	803: 3/4
	GRADE	805: 4
	GRADE	811: 5
	GRADE	900: 5/6
	GRADE	901: 4
	GRADE	902: 5
	GRADE	903: 4/5
• PILLING ON MARTINDALE ISO 12945-2:2000	500 RUBS	4/5
	1000 RUBS	4
	2000 RUBS	3/4
	5000 RUBS	3/4
• COLOUR FASTNESS TO WATER ISO 105-E01	STAINING TO WOOL	5
	STAINING TO ACRYL	5
	STAINING TO POLYESTER	4/5
	STAINING TO NYLON	4/5
	STAINING TO COTTON	4/5
	STAINING TO ACETATE	4/5
	CHANGE IN COLOUR	4/5