



Sunbrella outdoor furniture fabric

Product specifications

Fiber content 100% solution dyed acrylic

Spray test	ISO 4920	4 / 5
Water column (Schmerber)	ISO 811	200 mm minimum
Oil resistance	ISO 14419	5 / 8
Weight	ASTM D-3776-96	265 g/m2 +/- 10g
Width	ASTM D-3774-96	138cm +/- 1 cm
Breaking Strength	NF G 07149	Warp 7.1 daN Weft 3.0 daN
Seam slippage (at 7 stitches min/inch)	ASTM D-4034-92	Warp 90+ lbf. Weft 90+ lbf.
UV resistance	ISO 105 B02	7 to 8 / 8
Weathering & Color fastness	ISO 105 B04 Xenon Weatherometer	7 to 8 / 8 5/4 little or no change
Color resistance washing	ISO 105 C06 40°C	5 / 5
abrasion	ASTM D-4157_92	15 000 cycles
flammability	U.F.A.C. (US norm)	Class 1 pass
finishing	stain and water repellent finish ELF ATOCHEM Perlgard® DO NOT CONTAIN PFOS (perfluorooctanyl sulfonate) Label Öeko-Tex standard 100	
Dry & Wet Rubbing	ISO 105 X12	5 / 5